


NOTES: UNLESS OTHERWISE SPECIFIED  
 1. INTERPRET DRAWING IN ACCORDANCE WITH ASME Y14.5-1994.  
 △ PART TO BE SUPPLIED ON A CONTINUOUS REEL AS SHOWN. ONE BREAK AND NO SPLICES ALLOWED WITHIN A REEL.  
 3. DELETED.  
 △ MATERIAL: COPPER ALLOY  
 △ FINISH: SEE PART NUMBER BREAKDOWN

**PART NUMBER BREAKDOWN**  
 7-13340 - [ ] [ ]

FINISH: POST PLATED  
 OMIT STD = .000120" [3.05 MICRONS] MIN MATTE SnPb OVER .000050" [1.27 MICRONS] MIN Ni.  
 TT = .000160" [4.06 MICRONS] MIN MATTE Sn (LEAD FREE) OVER .000080" [2.03 MICRONS] MIN Ni. (RHHS COMPLIANT).

TYPE: TAB  
 THICKNESS:  
 5 = .020  
 8 = .031



PART NUMBER	"A"	RECOMMENDED DRILL HOLE SIZE	RECOMMENDED COPPER HOLE SIZE	RECOMMENDED FINISHED HOLE SIZE	QTY PER REEL △
7-13340-5	Ø .020±.001	Ø .055±.002	Ø .051±.002	Ø (.050 [1.27])	12,000
7-13340-5TT	[0.51 ±.25]	[1.40±0.05]	[1.30±0.05]	REF	
7-13340-8	Ø .031±.001	Ø .060±.002	Ø .056±.002	Ø (.055 [1.40])	8,000
7-13340-BTT	[0.79 ±.25]	[1.52±0.05]	[1.42±0.05]	REF	

REV	REVISION RECORD	ECN	BY	APPRO	DATE
A	INITIAL RELEASE	13776	MAC	PB	10/05/95
B	PER ECN	14457	MAC	PB	10/01/96
C	REVISED & REDRAWN PER DWG 104408	505010	SHI	PB	07/27/05
D	UPDATED REC. HOLE INFO	505003	RJB	RJB	06/12/07
E	REMOVED INCORRECT SCORE FEATURE	506300	RJB	RJB	08/18/11

**CUSTOMER DRAWING**

autosplice

187 QUICK DISCONNECT

QAE89 C7-13340-1111 E